



817.277.8566 • 800. 342.2409  
 Fax 817.275.2335  
 www.pieresearch.com

The table below illustrates the recommended number of Quick-Lock™ wheels to be used on a per shaft basis. The actual number can vary subject to the number of verticle bars of the reinforcing steel cage and the weight of the cage. The structural engineer is the governing authority. When in doubt, please check with the structural engineer.

<b>Recommended Quick-Lock™ Wheels per Reinforcing Cage</b>					
<i>Pier Shaft Depth in Feet</i>	<i>Per Shaft Diameter in Inches</i>				
	<b>Under 30"</b>	<b>31" to 48"</b>	<b>49" to 72"</b>	<b>73" to 96"</b>	<b>97" to 120"</b>
0' to 12'	9	12	18	24	30
13' to 24'	14	18	27	36	45
25' to 36'	18	24	36	48	45
37' to 48'	23	30	45	60	75
49' to 60'	27	36	54	72	90
61' to 72'	32	42	63	84	105
73' to 84'	36	48	72	96	120
85' to 96'	41	54	81	108	135
97' to 108'	45	60	90	120	150
109' to 120'	54	72	108	144	180
121' to 132'	59	78	117	156	195
133' to 144'	63	84	126	168	210

Visit us at [www.pieresearch.com](http://www.pieresearch.com) for suggested specifications and other information.